



Beny 2 Guns DC EV Charging Station

40kW -262kW



Datasheet

Zhejiang Benyi New Energy Co.,Ltd.

Shuanghuanglou Industrial Zone, Beibaixiang Yueqing,zhejiang P.R. China

TEL: +86-577-5717 7008 FAX: +86-577-5717 7007

✉ info@evb.com 🏠 Importer:xxxxxxx

🌐 www.evb.com 📍 Address:xxxxxxx

♻️ This catalogue has been printed on ecological paper.
© Zhejiang Benyi New Energy Co.,Ltd. All rights reserved.



VERSION: 20250708-01









WWW.EVB.COM

Product Overview

The Beny DC EV Charging Station boasts a remarkable 21-inch touch screen for effortless control. It comes with a range of certifications including CE, RCM, UKCA, TUV, and RoHS, and offers robust full protection features. With convenient APP control and Ethernet/4G/WiFi connectivity, you can charge your EV with confidence and efficiency.



Product Advantages

-  IP55 Rating
-  4G
-  Full Protection
-  Ethernet/4G/WiFi
-  OCPP 1.6J
-  7-inch Touch Screen
-  RFID
-  APP Control

Model Selection


DC EV Charging Station



Structure Description			
Shell Material	Galvanized Sheet		
Dimension	800*800*1800(L*W*H mm)		
Packing Dimension	1050*1100*2035(L*W*H mm)		
Weight	≤300kG	≤320kG	≤340kG
Installation Method	Floor-stand Type		
Cable Routing	Bottom Inlet Wiring, Up Outlet Wiring		
Total length of gun cable	5 m		
Charging Outlets	Double(CCS1+CCS1) Double (CCS1+CHADEMO) Double(CCS2+GBT) Double(CHADEMO+CHADEMO) Double(CCS2+CCS2)	Double (CCS2+CHADEMO) Double(CHADEMO+GBT) Double(CCS1+CCS2) Double(CCS1+GBT) Double(GBT+GBT)	Double (CCS1+NACS) Double(CCS2+NACS) Double(GBT+NACS) Double(CHADEMO+NACS) Double(NACS+NACS)
Connectivity Authorization	RFID, App		
Screen	21 Inch LCD Screen/LED Light		
Electrical Specification			
AC Input Voltage	AC380V-415V, 3P+N+PE		
Rated Input Current	68A	102A	135A
Input Frequency	50Hz/60Hz		
Consumption	≤24W		
Rated Power	40kW	60kW	80kW
Output Voltage Range	CCS1/CCS2/GBT/NACS: 150Vdc -1000Vdc;CHADEMO: 150Vdc -500Vdc		
Output Current	CCS1/CCS2:0~133A; GBT/NACS:0~133A; CHADEMO:0~150A	CCS1/CCS2:0~200A; GBT/NACS:0~200A; CHADEMO:0~150A	CCS1/CCS2:0~250A; GBT/NACS:0~250A; CHADEMO:0~150A
Efficiency	≥95%		
Power Factor	≥0.99(load:100%)		

Functionate Design	
User Interface	Emergency Stop Button,LED Indicator,Card Swiping,Touch Screen
Charging Stands	EN IEC 61851-1: 2019, IEC 61851-1: 2017, EN 61851-23: 2014, IEC 61851-23: 2014, EN 61851-24: 2014, IEC 61851-24: 2014, EN IEC 61000-6-2: 2019, EN IEC 61000-6-4:2019, EN IEC 61851-21-2: 2021
Communication	
OCPP	OCPP 1.6J
Network Interface	Ethernet/4G/WiFi
RF Parameters	
LTE-FDD Operating Frequency	B1/B2/B3/B4/B5/B7/B8/B12/B13/B18/B19/B20/B25/B26/B28
LTE-TDD Operating Frequency	B38/B39/B40/B41
UMTS Operating Frequency	B1/B2/B4/B5/B6/B8/B19
MIFARE Operating Frequency	13.56MHz±7K
2.4G WI-FI Operating Frequency	2412MHz-2484MHz
2.4G WI-FI Maximum Transmit Power	20.5 dBm
WCDMA Maximum Transmit Power	24 dBm +1/-3 dB
LTE-FDD Maximum Transmit Power	23 dBm±2 dB
LTE-TDD Maximum Transmit Power	23 dBm±2 dB
MIFARE Maximum Transmit Power	14.05dBuA/m
Environment Condition	
Application Place	Indoor/Outdoor
Working Altitude	<2000m
Storage Temperature	-30°C~+85°C
Working Temperature	-30°C~+50°C
Working Humidity	5%~95%
Protection Level	IP55 IK10(Screen IK08)
Natural Cooling	Forced-air Cooling
Security Design	Over/Under Voltage Protection, Overload Protection, Current Leakage Protection, Grounding Protection, Over Temp Protection, Lightening Surge Protection

Model Selection



Structure Description	
Shell Material	Galvanized Sheet
Dimension	800*800*1800(L*W*H mm)
Packing Dimension	1050*1100*2035(L*W*H mm)
Weight	≤340kG ≤360kG ≤380kG
Installation Method	Floor-stand Type
Cable Routing	Bottom Inlet Wiring, Up Outlet Wiring
Total length of gun cable	5 m
Charging Outlets	Double(CCS1+CCS1) Double (CCS2+CHADEMO) Double (CCS1+NACS) Double (CCS1+CHADEMO) Double(CHADEMO+GBT) Double(CCS2+NACS) Double(CCS2+GBT) Double(CCS1+CCS2) Double(GBT+NACS) Double(CHADEMO+CHADEMO) Double(CCS1+GBT) Double(CHADEMO+NACS) Double(CCS2+CCS2) Double(GBT+GBT) Double(NACS+NACS)
Connectivity Authorization	RFID, App
Screen	21 Inch LCD Screen/LED Light
Electrical Specification	
AC Input Voltage	AC380V-415V, 3P+N+PE
Rated Input Current	152A 203A 254A
Input Frequency	50Hz/60Hz
Consumption	≤24W
Rated Power	90kW 120kW 150kW
Output Voltage Range	CCS1/CCS2/GBT/NACS: 150Vdc ~1000Vdc; CHADEMO: 150Vdc ~ 500Vdc
Output Current	CCS1/CCS2/GBT/NACS: 0~250A; CHADEMO: 0~150A
Efficiency	≥95%
Power Factor	≥0.99(load:100%)

Functionate Design	
User Interface	Emergency Stop Button, LED Indicator, Card Swiping, Touch Screen
Charging Stands	EN IEC 61851-1: 2019, IEC 61851-1: 2017, EN 61851-23: 2014, IEC 61851-23: 2014, EN 61851-24: 2014, IEC 61851-24: 2014, EN IEC 61000-6-2: 2019, EN IEC 61000-6-4: 2019, EN IEC 61851-21-2: 2021
Communication	
OCPP	OCPP 1.6J
Network Interface	Ethernet/4G/WiFi
RF Parameters	
LTE-FDD Operating Frequency	B1/B2/B3/B4/B5/B7/B8/B12/B13/B18/B19/B20/B25/B26/B28
LTE-TDD Operating Frequency	B38/B39/B40/B41
UMTS Operating Frequency	B1/B2/B4/B5/B6/B8/B19
MIFARE Operating Frequency	13.56MHz±7K
2.4G WI-FI Operating Frequency	2412MHz-2484MHz
2.4G WI-FI Maximum Transmit Power	20.5 dBm
WCDMA Maximum Transmit Power	24 dBm +1/-3 dB
LTE-FDD Maximum Transmit Power	23 dBm±2 dB
LTE-TDD Maximum Transmit Power	23 dBm±2 dB
MIFARE Maximum Transmit Power	14.05dBuA/m
Environment Condition	
Application Place	Indoor/Outdoor
Working Altitude	<2000m
Storage Temperature	-30°C~+85°C
Working Temperature	-30°C~+50°C
Working Humidity	5%~95%
Protection Level	IP55 IK10(Screen IK08)
Natural Cooling	Forced-air Cooling
Security Design	Over/Under Voltage Protection, Overload Protection, Current Leakage Protection, Grounding Protection, Over Temp Protection, Lightening Surge Protection

Model Selection



Structure Description	
Shell Material	Galvanized Sheet
Dimension	800*800*1800(L*W*H mm)
Packing Dimension	1050*1100*2035(L*W*H mm)
Weight	≤380kG ≤400kG ≤420kG
Installation Method	Floor-stand Type
Cable Routing	Bottom Inlet Wiring, Up Outlet Wiring
Total length of gun cable	5 m
Charging Outlets	Double(CCS1+CCS1) Double (CCS2+CHADEMO) Double (CCS1+NACS) Double (CCS1+CHADEMO) Double(CHADEMO+GBT) Double(CCS2+NACS) Double(CCS2+GBT) Double(CCS1+CCS2) Double(GBT+NACS) Double(CHADEMO+CHADEMO) Double(CCS1+GBT) Double(CHADEMO+NACS) Double(CCS2+CCS2) Double(GBT+GBT) Double(NACS+NACS)
Connectivity Authorization	RFID, App
Screen	21 Inch LCD Screen/LED Light
Electrical Specification	
AC Input Voltage	AC380V-415V, 3P+N+PE
Rated Input Current	270A 304A 355A
Input Frequency	50Hz/60Hz
Consumption	≤24W
Rated Power	160kW 180kW 210kW
Output Voltage Range	CCS1/CCS2/GBT/NACS: 150Vdc ~1000Vdc; CHADEMO: 150Vdc ~ 500Vdc
Output Current	CCS1/CCS2/GBT/NACS: 0~250A; CHADEMO: 0~150A
Efficiency	≥95%
Power Factor	≥0.99(load:100%)

Functionate Design	
User Interface	Emergency Stop Button, LED Indicator, Card Swiping, Touch Screen
Charging Stands	EN IEC 61851-1: 2019, IEC 61851-1: 2017, EN 61851-23: 2014, IEC 61851-23: 2014, EN 61851-24: 2014, IEC 61851-24: 2014, EN IEC 61000-6-2: 2019, EN IEC 61000-6-4: 2019, EN IEC 61851-21-2: 2021
Communication	
OCPP	OCPP 1.6J
Network Interface	Ethernet/4G/WiFi
RF Parameters	
LTE-FDD Operating Frequency	B1/B2/B3/B4/B5/B7/B8/B12/B13/B18/B19/B20/B25/B26/B28
LTE-TDD Operating Frequency	B38/B39/B40/B41
UMTS Operating Frequency	B1/B2/B4/B5/B6/B8/B19
MIFARE Operating Frequency	13.56MHz±7K
2.4G WI-FI Operating Frequency	2412MHz-2484MHz
2.4G WI-FI Maximum Transmit Power	20.5 dBm
WCDMA Maximum Transmit Power	24 dBm +1/-3 dB
LTE-FDD Maximum Transmit Power	23 dBm±2 dB
LTE-TDD Maximum Transmit Power	23 dBm±2 dB
MIFARE Maximum Transmit Power	14.05dBuA/m
Environment Condition	
Application Place	Indoor/Outdoor
Working Altitude	<2000m
Storage Temperature	-30°C~+85°C
Working Temperature	-30°C~+50°C
Working Humidity	5%~95%
Protection Level	IP55 IK10(Screen IK08)
Natural Cooling	Forced-air Cooling
Security Design	Over/Under Voltage Protection, Overload Protection, Current Leakage Protection, Grounding Protection, Over Temp Protection, Lightning Surge Protection

Model Selection

DC EV Charging Station

BDC240-D



Structure Description

Shell Material	Galvanized Sheet		
Dimension	800*800*1800(L*W*H mm)		
Packing Dimension	1050*1100*2035(L*W*H mm)		
Weight	≤440kg		
Installation Method	Floor-stand Type		
Cable Routing	Bottom Inlet Wiring, Up Outlet Wiring		
Total length of gun cable	5 m		
Charging Outlets	Double(CCS1+CCS1) Double (CCS1+CHADEMO) Double(CCS2+GBT) Double(CHADEMO+CHADEMO) Double(CCS2+CCS2)	Double (CCS2+CHADEMO) Double(CHADEMO+GBT) Double(CCS1+CCS2) Double(CCS1+GBT) Double(GBT+GBT)	Double (CCS1+NACS) Double(CCS2+NACS) Double(GBT+NACS) Double(CHADEMO+NACS) Double(NACS+NACS)
Connectivity Authorization	RFID, App		
Screen	21 Inch LCD Screen/LED Light		

Electrical Specification

AC Input Voltage	AC380V-415V, 3P+N+PE
Rated Input Current	406A
Input Frequency	50Hz/60Hz
Consumption	≤24W
Rated Power	240kW
Output Voltage Range	CCS1/CCS2/GBT/NACS: 150Vdc ~1000Vdc;CHADEMO: 150Vdc ~ 500Vdc
Output Current	CCS1/CCS2/GBT/NACS:0~250A;CHADEMO:0~150A
Efficiency	≥95%
Power Factor	≥0.99(load:100%)

Functionate Design

User Interface	Emergency Stop Button,LED Indicator,Card Swiping,Touch Screen
Charging Stands	EN IEC 61851-1: 2019, IEC 61851-1: 2017, EN 61851-23: 2014, IEC 61851-23: 2014, EN 61851-24: 2014, IEC 61851-24: 2014, EN IEC 61000-6-2: 2019, EN IEC 61000-6-4:2019, EN IEC 61851-21-2: 2021

Communication

OCPP	OCPP 1.6J
Network Interface	Ethernet/4G/WiFi

RF Parameters

LTE-FDD Operating Frequency	B1/B2/B3/B4/B5/B7/B8/B12/B13/B18/B19/B20/B25/B26/B28
LTE-TDD Operating Frequency	B38/B39/B40/B41
UMTS Operating Frequency	B1/B2/B4/B5/B6/B8/B19
MIFARE Operating Frequency	13.56MHz±7K
2.4G WI-FI Operating Frequency	2412MHz-2484MHz
2.4G WI-FI Maximum Transmit Power	20.5 dBm
WCDMA Maximum Transmit Power	24 dBm +1/-3 dB
LTE-FDD Maximum Transmit Power	23 dBm±2 dB
LTE-TDD Maximum Transmit Power	23 dBm±2 dB
MIFARE Maximum Transmit Power	14.05dBuA/m

Environment Condition

Application Place	Indoor/Outdoor
Working Altitude	<2000m
Storage Temperature	-30°C~+85°C
Working Temperature	-30°C~+50°C
Working Humidity	5%~95%
Protection Level	IP55 IK10(Screen IK08)
Natural Cooling	Forced-air Cooling
Security Design	Over/Under Voltage Protection, Overload Protection, Current Leakage Protection, Grounding Protection, Over Temp Protection, Lightening Surge Protection

Model Selection

DC EV Charging Station	BADC52-S	BADC62-S	BADC82-S
------------------------	----------	----------	----------



Structure Description			
Shell Material	Galvanized Sheet		
Dimension	800*800*1800(L*W*H mm)		
Packing Dimension	1050*1100*2035(L*W*H mm)		
Weight	≤300kG	≤320kG	≤340kG
Installation Method	Floor-stand Type		
Cable Routing	Bottom Inlet Wiring, Up Outlet Wiring		
Total length of gun cable	5 m		
Charging Outlets	Double(CCS2+AC) Double(GBT+AC)	Double(CHADEMO+AC) Double(NACS+AC)	Double(CCS1+AC)
Connectivity Authorization	RFID, App		
Screen	21 Inch LCD Screen/LED Light		
Electrical Specification			
AC Input Voltage	AC380V-415V, 3P+N+PE		
Rated Input Current	88A	134A	139A
Input Frequency	50Hz/60Hz		
Consumption	≤24W		
Rated Power	52kW	62kW	82kW
Output Voltage Range	CCS1/CCS2/GBT/NACS: 150Vdc ~1000Vdc; CHADEMO: 150Vdc ~ 500Vdc		
Output Current	CCS1/CCS2: 0~100A GBT/NACS: 0~100A CHADEMO: 0~100A AC:0-32A	CCS1/CCS2: 0~133A GBT/NACS: 0~133A CHADEMO: 0~133A AC:0-32A	CCS1/CCS2: 0~200A GBT/NACS: 0~200A CHADEMO: 0~150A AC:0-32A
Efficiency	≥95%		
Power Factor	≥0.99(load:100%)		

Functionate Design	
User Interface	Emergency Stop Button, LED Indicator, Card Swiping, Touch Screen
Charging Stands	EN IEC 61851-1: 2019, IEC 61851-1: 2017, EN 61851-23: 2014, IEC 61851-23: 2014, EN 61851-24: 2014, IEC 61851-24: 2014, EN IEC 61000-6-2: 2019, EN IEC 61000-6-4: 2019, EN IEC 61851-21-2: 2021
Communication	
OCPP	OCPP 1.6J
Network Interface	Ethernet/4G/WiFi
RF Parameters	
LTE-FDD Operating Frequency	B1/B2/B3/B4/B5/B7/B8/B12/B13/B18/B19/B20/B25/B26/B28
LTE-TDD Operating Frequency	B38/B39/B40/B41
UMTS Operating Frequency	B1/B2/B4/B5/B6/B8/B19
MIFARE Operating Frequency	13.56MHz±7K
2.4G WI-FI Operating Frequency	2412MHz-2484MHz
2.4G WI-FI Maximum Transmit Power	20.5 dBm
WCDMA Maximum Transmit Power	24 dBm +1/-3 dB
LTE-FDD Maximum Transmit Power	23 dBm±2 dB
LTE-TDD Maximum Transmit Power	23 dBm±2 dB
MIFARE Maximum Transmit Power	14.05dBuA/m
Environment Condition	
Application Place	Indoor/Outdoor
Working Altitude	<2000m
Storage Temperature	-30°C~+85°C
Working Temperature	-30°C~+50°C
Working Humidity	5%~95%
Protection Level	IP55 IK10(Screen IK08)
Natural Cooling	Forced-air Cooling
Security Design	Over/Under Voltage Protection, Overload Protection, Current Leakage Protection, Grounding Protection, Over Temp Protection, Lightening Surge Protection

Model Selection

DC EV Charging Station	BADC102-S	BADC112-S	BADC142-S
------------------------	-----------	-----------	-----------



Structure Description	
Shell Material	Galvanized Sheet
Dimension	800*800*1800(L*W*H mm)
Packing Dimension	1050*1100*2035(L*W*H mm)
Weight	≤360kG ≤360kG ≤380kG
Installation Method	Floor-stand Type
Cable Routing	Bottom Inlet Wiring,Up Outlet Wiring
Total length of gun cable	5 m
Charging Outlets	Double(CCS2+AC) Double(CHADEMO+AC) Double(CCS1+AC) Double(GBT+AC) Double(NACS+AC)
Connectivity Authorization	RFID, App
Screen	21 Inch LCD Screen/LED Light
Electrical Specification	
AC Input Voltage	AC380V-415V, 3P+N+PE
Rated Input Current	173A 190A 240A
Input Frequency	50Hz/60Hz
Consumption	≤24W
Rated Power	102kW 112kW 142kW
Output Voltage Range	CCS1/CCS2/GBT/NACS: 150Vdc ~1000Vdc;CHADEMO: 150Vdc ~ 500Vdc
Output Current	CCS1/CCS2/GBT/NACS:0~250A;CHADEMO:0~150A;AC:0-32A
Efficiency	≥95%
Power Factor	≥0.99(load:100%)

Functionate Design	
User Interface	Emergency Stop Button,LED Indicator,Card Swiping,Touch Screen
Charging Stands	EN IEC 61851-1: 2019, IEC 61851-1: 2017, EN 61851-23: 2014, IEC 61851-23: 2014, EN 61851-24: 2014, IEC 61851-24: 2014, EN IEC 61000-6-2: 2019, EN IEC 61000-6-4:2019, EN IEC 61851-21-2: 2021
Communication	
OCPP	OCPP 1.6J
Network Interface	Ethernet/4G/WiFi
RF Parameters	
LTE-FDD Operating Frequency	B1/B2/B3/B4/B5/B7/B8/B12/B13/B18/B19/B20/B25/B26/B28
LTE-TDD Operating Frequency	B38/B39/B40/B41
UMTS Operating Frequency	B1/B2/B4/B5/B6/B8/B19
MIFARE Operating Frequency	13.56MHz±7K
2.4G WI-FI Operating Frequency	2412MHz-2484MHz
2.4G WI-FI Maximum Transmit Power	20.5 dBm
WCDMA Maximum Transmit Power	24 dBm +1/-3 dB
LTE-FDD Maximum Transmit Power	23 dBm±2 dB
LTE-TDD Maximum Transmit Power	23 dBm±2 dB
MIFARE Maximum Transmit Power	14.05dBuA/m
Environment Condition	
Application Place	Indoor/Outdoor
Working Altitude	<2000m
Storage Temperature	-30°C~+85°C
Working Temperature	-30°C~+50°C
Working Humidity	5%~95%
Protection Level	IP55 IK10(Screen IK08)
Natural Cooling	Forced-air Cooling
Security Design	Over/Under Voltage Protection, Overload Protection, Current Leakage Protection, Grounding Protection, Over Temp Protection, Lightening Surge Protection

Model Selection


DC EV Charging Station	BADC172-S	BADC182-S	BADC202-S
------------------------	-----------	-----------	-----------



Structure Description	
Shell Material	Galvanized Sheet
Dimension	800*800*1800(L*W*H mm)
Packing Dimension	1050*1100*2035(L*W*H mm)
Weight	≤400kG ≤400kG ≤420kG
Installation Method	Floor-stand Type
Cable Routing	Bottom Inlet Wiring,Up Outlet Wiring
Total length of gun cable	5 m
Charging Outlets	Double(CCS2+AC) Double(CHADEMO+AC) Double(CCS1+AC) Double(GBT+AC) Double(NACS+AC)
Connectivity Authorization	RFID, App
Screen	21 Inch LCD Screen/LED Light
Electrical Specification	
AC Input Voltage	AC380V-415V, 3P+N+PE
Rated Input Current	291A 302A 342A
Input Frequency	50Hz/60Hz
Consumption	≤24W
Rated Power	172kW 182kW 202kW
Output Voltage Range	CCS1/CCS2/GBT/NACS: 150Vdc ~1000Vdc;CHADEMO: 150Vdc ~ 500Vdc
Output Current	CCS1/CCS2/GBT/NACS: 0~250A;CHADEMO: 0~150A;AC:0-32A
Efficiency	≥95%
Power Factor	≥0.99(load:100%)

Functionate Design	
User Interface	Emergency Stop Button,LED Indicator,Card Swiping,Touch Screen
Charging Stands	EN IEC 61851-1: 2019, IEC 61851-1: 2017, EN 61851-23: 2014, IEC 61851-23: 2014, EN 61851-24: 2014, IEC 61851-24: 2014, EN IEC 61000-6-2: 2019, EN IEC 61000-6-4:2019, EN IEC 61851-21-2: 2021
Communication	
OCPP	OCPP 1.6J
Network Interface	Ethernet/4G/WiFi
RF Parameters	
LTE-FDD Operating Frequency	B1/B2/B3/B4/B5/B7/B8/B12/B13/B18/B19/B20/B25/B26/B28
LTE-TDD Operating Frequency	B38/B39/B40/B41
UMTS Operating Frequency	B1/B2/B4/B5/B6/B8/B19
MIFARE Operating Frequency	13.56MHz±7K
2.4G WI-FI Operating Frequency	2412MHz-2484MHz
2.4G WI-FI Maximum Transmit Power	20.5 dBm
WCDMA Maximum Transmit Power	24 dBm +1/-3 dB
LTE-FDD Maximum Transmit Power	23 dBm±2 dB
LTE-TDD Maximum Transmit Power	23 dBm±2 dB
MIFARE Maximum Transmit Power	14.05dBuA/m
Environment Condition	
Application Place	Indoor/Outdoor
Working Altitude	<2000m
Storage Temperature	-30°C~+85°C
Working Temperature	-30°C~+50°C
Working Humidity	5%~95%
Protection Level	IP55 IK10(Screen IK08)
Natural Cooling	Forced-air Cooling
Security Design	Over/Under Voltage Protection, Overload Protection, Current Leakage Protection, Grounding Protection, Over Temp Protection, Lightening Surge Protection

Model Selection

DC EV Charging Station	BADC232-S	BADC262-S
		
Structure Description		
Shell Material	Galvanized Sheet	
Dimension	800*800*1800(L*W*H mm)	
Packing Dimension	1050*1100*2035(L*W*H mm)	
Weight	≤460kG	≤480kG
Installation Method	Floor-stand Type	
Cable Routing	Bottom Inlet Wiring, Up Outlet Wiring	
Total length of gun cable	5 m	
Charging Outlets	Double(CCS2+AC) Double(GBT+AC)	Double(CHADEMO+AC) Double(NACS+AC) Double(CCS1+AC)
Connectivity Authorization	RFID, App	
Screen	21 Inch LCD Screen/LED Light	
Electrical Specification		
AC Input Voltage	AC380V-415V, 3P+N+PE	
Rated Input Current	392A	443A
Input Frequency	50Hz/60Hz	
Consumption	≤24W	
Rated Power	232kW	262kW
Output Voltage Range	CCS1/CCS2/GBT/NACS: 150Vdc ~1000Vdc; CHADEMO: 150Vdc ~ 500Vdc	
Output Current	CCS1/CCS2/GBT/NACS: 0~250A; CHADEMO: 0~ 150A; AC: 0-32A	
Efficiency	≥95%	
Power Factor	≥0.99(load:100%)	

Functionate Design	
User Interface	Emergency Stop Button, LED Indicator, Card Swiping, Touch Screen
Charging Stands	EN IEC 61851-1: 2019, IEC 61851-1: 2017, EN 61851-23: 2014, IEC 61851-23: 2014, EN 61851-24: 2014, IEC 61851-24: 2014, EN IEC 61000-6-2: 2019, EN IEC 61000-6-4: 2019, EN IEC 61851-21-2: 2021
Communication	
OCPP	OCPP 1.6J
Network Interface	Ethernet/4G/WiFi
RF Parameters	
LTE-FDD Operating Frequency	B1/B2/B3/B4/B5/B7/B8/B12/B13/B18/B19/B20/B25/B26/B28
LTE-TDD Operating Frequency	B38/B39/B40/B41
UMTS Operating Frequency	B1/B2/B4/B5/B6/B8/B19
MIFARE Operating Frequency	13.56MHz±7K
2.4G WI-FI Operating Frequency	2412MHz-2484MHz
2.4G WI-FI Maximum Transmit Power	20.5 dBm
WCDMA Maximum Transmit Power	24 dBm +1/-3 dB
LTE-FDD Maximum Transmit Power	23 dBm±2 dB
LTE-TDD Maximum Transmit Power	23 dBm±2 dB
MIFARE Maximum Transmit Power	14.05dBuA/m
Environment Condition	
Application Place	Indoor/Outdoor
Working Altitude	<2000m
Storage Temperature	-30°C~+85°C
Working Temperature	-30°C~+50°C
Working Humidity	5%~95%
Protection Level	IP55 IK10(Screen IK08)
Natural Cooling	Forced-air Cooling
Security Design	Over/Under Voltage Protection, Overload Protection, Current Leakage Protection, Grounding Protection, Over Temp Protection, Lightening Surge Protection